

# **Helmholtz Imaging Conference 2022**

Tuesday, May 31, 2022 - Wednesday, June 1, 2022

Axica



## **Book of Abstracts**



# Contents

Neuroimaging-Genetics bridge for better understanding of human brain organization . . .	1
Structural Biology of SARS-CoV-2: Making the Invisible Enemy Visible . . . . .	1
Space-Based Synthetic Aperture Radar (SAR) Imaging for Climate Research and Environmental Monitoring . . . . .	2
Improving Explainability of Disentangled Representations using Multipath-Attribution Mappings . . . . .	3
X-roads of Imaging and Data Science: Projects to Accelerate Imaging . . . . .	3
Nuclear Verification from Space - Change Detection using Machine Learning and Sentinel-2 Imagery . . . . .	4
Multi-axes fusing for uncertainty estimation and improved segmentation of biodegradable bone implants in SR $\mu$ CTs . . . . .	4
Towards distributed imaging for autonomous seismic surveys in multi-agent networks . .	5
AI-based Evaluation of cardiac real-time MRI with congenital heart disease . . . . .	6
Initial results using neuroimaging features to predict the genetic risk of RLS . . . . .	6
Using k-Means to identify Coronal Holes on AIA/SDO Images . . . . .	7
Advances in landslide analysis using remote sensing: Results from Multisat4slows project	7
Helmholtz Imaging Modalities and Network . . . . .	8
Performance Portable Reconstruction of Ptychography Data with the Alpaka C++ Library	8
Computational Imaging for Art investigation and for Neuroscience . . . . .	9
Challenges for imaging. How do we deal with them? . . . . .	10
Helmholtz Imaging . . . . .	10
Poster Session . . . . .	10
Proposal of a Joint Inversion Imaging Approach for the Estimation of Brain Myelin Content using MRI . . . . .	12
Advances in landslide analysis using remote sensing: Results from Multisat4slows project	12

Deep Learning for Lithological Point Cloud Segmentation . . . . .	13
Exploring Digital Twin of the Earth. Challenges in visualization of kilometer scale Earth System model simulations . . . . .	13
Deep-Learning Meets Microbial Live-Cell Imaging: Powerful Analysis Workflows from Annotation to Prediction . . . . .	13
Using k-Means to identify Coronal Holes on AIA/SDO Images . . . . .	14
Best Scientific Image Awards . . . . .	15
Metrics Reloaded – A new recommendation framework for biomedical image analysis validation . . . . .	15
Multi-beam X-ray ptychography using coded probes . . . . .	15
Deep Learning for 3D Lithological Point Cloud Segmentation . . . . .	16
Welcome and introduction . . . . .	16
Mind the gap on bringing research and politics closer together . . . . .	16
Looking to the future . . . . .	17
Next Big Challenges for Imaging Science . . . . .	17
AI for Imaging . . . . .	17
Big Data & Scalability . . . . .	17

## Poster Session / 3

## Neuroimaging-Genetics bridge for better understanding of human brain organization

**Authors:** Talip Yasir Demirtas<sup>1</sup>; Leonard Sasse<sup>1</sup>; Ecehan Abdik<sup>2</sup>; Amir Omidvarnia<sup>1</sup>; Tunahan Cakir<sup>2</sup>; Federico Raimondo<sup>1</sup>; Kaustubh R. Patil<sup>3</sup>

<sup>1</sup> *Institute of Neuroscience and Medicine, Brain and Behavior (INM-7), Research Center Jülich, Jülich, Germany.*

<sup>2</sup> *Department of Bioengineering, Gebze Technical University, Kocaeli, Turkey.*

<sup>3</sup> *Institute of Neuroscience and Medicine, Brain and Behavior (INM-7), Research Center Jülich, Jülich, Germany*

**Corresponding Author:** y.demirtas@fz-juelich.de

Magnetic Resonance Imaging (MRI) has promising potential for clinical translation due to its non-invasive nature and high spatial resolution. MRI offers structural and functional measurement modalities which capture the fundamental principles of human brain organization and variability in neurological disorders. Combining information from the MRI-derived phenomics and DNA-derived transcriptomics can provide a holistic view of human brain organization and deeper insights into disease pathologies.

Here, we aimed to develop a Python package called nimgen to bridge MRI organization and gene expression data. The package allows extracting gene expression levels for parcellations commonly used in the neuroimaging community leveraging the 62,000 probes from the Allen Human Brain Atlas (AHBA) [1] using the abagen package [2]. Then each gene's expression levels can be correlated to an MRI marker of interest. False discovery rate control is applied resulting in a statistically significantly correlated subset of genes. With the assistance of gene enrichment analysis tools (i.e. WebGestalt, [3]), the significant genes are examined to obtain higher-order biological processes. However, since increasing the number of parcels can inflate statistical significance, nimgen provides a permutation-testing approach based on BrainSMASH [4]. An efficient, reproducible, and rapid pipeline with several MRI markers may be constructed due to the nimgen package's modular design and functionality. Besides, this user-friendly package allows researchers to rapidly analyze NIfTI files with only a basic computational background and minimal effort. We hope that marker-specific candidate gene sets found by the nimgen package will help to better understand genetic makeup of the human brain and develop strategies for the diagnosis and treatment of diseases. Our codes are publicly available at <https://github.com/juaml/nimgen>. With the flexibility this software provides, we aim to create a comprehensive mapping of biological processes based on transcriptome and MRI measurements, leveraging state-of-the-art neuroimaging data repositories such as the Human Connectome Project (HCP) [5] S1200 release.

**Keywords:** Gene Expression, Bioinformatics, Neuroimaging

### References:

- [1] E. H. Shen, C. C. Overly, and A. R. Jones, "The Allen Human Brain Atlas: comprehensive gene expression mapping of the human brain," *Trends Neurosci.*, vol. 35, no. 12, pp. 711–714, 2012.
- [2] R. D. Markello, A. Arnatkevičiute, J.-B. Poline, B. D. Fulcher, A. Fornito, and B. Misic, "Standardizing workflows in imaging transcriptomics with the abagen toolbox," *Elife*, vol. 10, p. e72129, 2021.
- [3] Y. Liao, J. Wang, E. J. Jaehnig, Z. Shi, and B. Zhang, "WebGestalt 2019: gene set analysis toolkit with revamped UIs and APIs," *Nucleic Acids Res.*, vol. 47, no. W1, pp. W199–W205, 2019.
- [4] J. B. Burt, M. Helmer, M. Shinn, A. Anticevic, and J. D. Murray, "Generative modeling of brain maps with spatial autocorrelation," *NeuroImage*, vol. 220, p. 117038, Oct. 2020, doi: 10.1016/j.neuroimage.2020.117038.
- [5] D. C. Van Essen et al., "The Human Connectome Project: a data acquisition perspective," *Neuroimage*, vol. 62, no. 4, pp. 2222–2231, 2012.

## Keynote II / 4

## Structural Biology of SARS-CoV-2: Making the Invisible Enemy Visible

**Author:** Andrea Thorn<sup>1</sup>

<sup>1</sup> *Universität Hamburg*

During the COVID-19 pandemic, structural biologists rushed to solve the structures of the 28 proteins encoded by the SARS-CoV-2 genome in order to understand the viral life cycle and to enable structure-based drug design. In addition to the 204 previously solved structures from SARS-CoV-1, over 2000 structures covering 18 of the SARS-CoV-2 viral proteins were released in a span of a few months. These structural models serve as the basis for research to understand how the virus hijacks human cells, for structure-based drug design, and to aid in the development of vaccines. The Coronavirus Structural Task Force [1] rapidly categorized, evaluated and reviewed all of these experimental protein structures in order to help original authors and downstream users, for example Folding@Home, OpenPandemics, the EU JEDI COVID-19 challenge. We also created reviews, illustrations, animations and 3D printable models of the virus from these experimental results, which we distributed via [www.insidecorona.net](http://www.insidecorona.net). In the beginning, there were no tenured academics in the Coronavirus Structural Task Force; we were an ad hoc collaboration of 26 researchers across nine time zones, brought together by the desire to fight the pandemic. Still, we were able to rapidly establish a large network of COVID-19 related research, forge friendships and collaborations across national boundaries, spread knowledge about the structural biology of the virus and provide improved models for in-silico drug discovery projects. Now, after more than two years, we have consolidated our collective knowledge about the virus, and can leverage this insight for the question: What is next?

[1] Croll, T., Diederichs, K., Fischer, F., Fyfe, C., Gao, Y., Horrell, S., Joseph, A., Kandler, L., Kippes, O., Kirsten, F., Müller, K., Nolte, K., Payne, A., Reeves, M.G., Richardson, J., Santoni, G., Stüb, S., Tronrud, D., Williams, C., Thorn, A\*. (2021) Making the invisible enemy visible (2021) *Nature Structural & Molecular Biology* 28, 404–408 <https://doi.org/10.1038/s41594-021-00593-7>

**I want to give an oral presentation.:**

**I want to present a poster.:**

**Keynote I / 5**

## **Space-Based Synthetic Aperture Radar (SAR) Imaging for Climate Research and Environmental Monitoring**

Space-based Synthetic Aperture Radar (SAR) has been widely used for Earth remote sensing for more than 40 years. SAR is unique in its imaging capability: It provides high-resolution imaging independent from daylight, cloud cover and weather conditions for a multitude of applications ranging from geoscience and climate change research, environmental and Earth system monitoring, 2D and 3D mapping, change detection, 4D mapping (space and time), security-related applications up to planetary exploration. Therefore, it is predestined to monitor dynamic processes on the Earth's surface in a reliable, continuous and global way. SAR systems have a side-looking imaging geometry and are based on a pulsed radar installed on a moving platform. By means of a coherent processing of the received echo signal, a long synthetic aperture can be formed, which corresponds to a synthetic antenna length of a few hundred meters and even several kilometers in the airborne and spaceborne case, respectively. Since the length of the synthetic aperture increases with the platform height, the spatial resolution becomes independent on the distance to the target, making SAR a unique technique for space-based SAR Earth observation.

This talk first describes the principles of SAR imaging along with various application examples. Next, advanced techniques for SAR imaging like interferometry, polarimetry, tomography and holography are presented. In combination with the latest digital beamforming imaging techniques, a highly innovative spaceborne SAR mission, called Tandem-L, has been proposed for global observation of dynamic processes on the Earth's surface with hitherto unprecedented quality and resolution. The talk concludes with an outlook on the future of space-based SAR imaging.

**I want to give an oral presentation.:**

**I want to present a poster.:**

**Poster Session / 7**

## **Improving Explainability of Disentangled Representations using Multipath-Attribution Mappings**

**Author:** Lukas Klein<sup>1</sup>

**Co-authors:** João Carvalho <sup>2</sup>; Mennatallah El-Assady <sup>2</sup>; Joachim Buhmann <sup>2</sup>; Paolo Penna <sup>2</sup>; Paul Jäger <sup>1</sup>

<sup>1</sup> DKFZ, Helmholtz Imaging

<sup>2</sup> ETH Zürich

**Corresponding Author:** lukas.klein@dkfz-heidelberg.de

Explainable AI aims to render model behavior understandable by humans, which can be seen as an intermediate step in extracting causal relations from correlative patterns. Due to the high risk of possible fatal decisions in image-based clinical diagnostics, it is necessary to integrate explainable AI into these safety-critical systems. Current explanatory methods typically assign attribution scores to pixel regions in the input image, indicating their importance for a model's decision. However, they fall short when explaining why a visual feature is used. We propose a framework that utilizes interpretable disentangled representations for downstream-task prediction. Through visualizing the disentangled representations, we enable experts to investigate possible causation effects. Additionally, we deploy a multi-path attribution mapping for enriching and validating explanations. We demonstrate the effectiveness of our approach on a synthetic benchmark suite and two medical datasets.

**I want to give an oral presentation.:**

yes

**I want to present a poster.:**

yes

**Keynote III / 8**

## **X-roads of Imaging and Data Science: Projects to Accelerate Imaging**

**Author:** Wojtek Gosinski<sup>1</sup>

<sup>1</sup> CEO at National Imaging Facility (NIF), Australia

Medical research is increasingly dependent on the ability to capture, store, process, integrate, and analyse large volumes of data. Moreover, in the foreseeable future, the size of research studies will continue to increase, and the overarching driver is to improve research quality and to increase reproducibility. Large-scale studies require a step change in the way that data is treated.

The opportunities are accelerating with the common introduction of ML methods, such as convolutional neural networks, the information that can be quantitatively gathered from images will increase, and thus so will the value of imaging within the research lifecycle. ML-based image analysis can extract more information, with less human intervention, across larger study sizes.

This presentation will provide an overview of a number of Australian research infrastructure initiatives that attempt to bridge the gap between the instrument and computing capability, by providing imaging users with accessible, powerful and easy-to-use environments. I will present initiatives to integrate instruments, manage imaging research data at a national scale, provide crucial data analysis skills and accelerate the adoption of standards and machine learning techniques across areas such as structural biology and neuroimaging, and I will provide an overview of future data strategy being developed across the National Imaging Facility.

**I want to give an oral presentation.:**

**I want to present a poster.:**

**Poster Session / 9**

## **Nuclear Verification from Space - Change Detection using Machine Learning and Sentinel-2 Imagery**

**Authors:** Irmgard Niemeyer<sup>1</sup>; Lisa Beumer<sup>1</sup>

<sup>1</sup> *Forschungszentrum Jülich GmbH*

**Corresponding Author:** l.beumer@fz-juelich.de

Within the framework of the Nuclear Non-Proliferation Treaty, a system of safeguards was established under the authority of the International Atomic Energy Agency (IAEA) to prevent the proliferation of weapons of mass destruction. Satellite imagery is an integral part of the IAEA's monitoring and verification efforts as it can be used to monitor changes and activities in nuclear facilities worldwide. The EO big data with its sheer volume, its complexity and heterogeneity is accompanied by a number of challenges. Image-processing algorithms based on Data Science methods have achieved stunning achievements leading to a more effective and efficient data exploitation. However, turning EO data into valuable safeguards relevant information is an ongoing challenge due to the lack of labeled training data. In this work, we propose a method based on transfer learning to deploy a CNN that can effectively extract contextual image features, which are in turn used for change detection.

**I want to give an oral presentation.:**

no

**I want to present a poster.:**

yes

**Poster Session / 10**

## **Multi-axes fusing for uncertainty estimation and improved segmentation of biodegradable bone implants in SR $\mu$ CTs**

**Authors:** Ivo-Matteo Baltruschat<sup>None</sup>; Hanna  $\acute{C}$ wieka<sup>1</sup>



**Co-authors:** Diana Krüger <sup>1</sup>; Berit Zeller-Plumhoff <sup>1</sup>; Frank Schluenzen ; Regine Willumeit-Römer <sup>1</sup>; Julian Moosmann <sup>2</sup>; Philipp Heuser <sup>3</sup>

<sup>1</sup> *Institute of Metallic Biomaterials, Helmholtz-Zentrum hereon*

<sup>2</sup> *Helmholtz-Zentrum Hereon*

<sup>3</sup> *DESY/Helmholtz Imaging*

**Corresponding Author:** ivo.matteo.baltruschat@desy.de

Segmentation of synchrotron microtomograms (SR $\mu$ CTs) is very challenging, both for algorithmic solutions and for domain experts. To characterize biodegradable bone implants based on automatic segmentation, DESY and Hereon investigated the scaling of the 2D U-net for high-resolution volumes using three key model hyperparameters (i.e., model width, depth, and input size). To utilize the 3D information from the SR $\mu$ CTs, the prediction is made from multiple viewing directions and then fused by a voting method. In the evaluation, we compare the results by intersection over union (IoU). In summary, combined scaling of the U-net (i.e., all three model parameters are optimized together) and multi-axis prediction fusing with soft voting yields the highest IoU for the least abundant class. The multi-axes prediction allows the computation of uncertainty estimates with very low additional computational cost. Overall, the time needed to segment a single 3D SR $\mu$ CT is reduced by an order of magnitude.

**I want to give an oral presentation.:**

yes

**I want to present a poster.:**

yes

**Poster Session / 12**

## **Towards distributed imaging for autonomous seismic surveys in multi-agent networks**

**Author:** Ban-Sok Shin<sup>1</sup>

**Co-author:** Dmitriy Shutin <sup>1</sup>

<sup>1</sup> *German Aerospace Center*

**Corresponding Author:** ban-sok.shin@dlr.de

Distributed imaging is of high relevance for autonomous seismic surveys conducted by a multi-agent network. Such systems play an important role for future space missions to image near-surface anomalies such as lava tubes. The goal of distributed imaging is to obtain an estimate of the subsurface image at each agent locally via cooperation within the network. The image is resolved with respect to a physical parameter of the subsurface such as seismic wave speed or material density. We proposed a distributed version of the full waveform inversion (FWI) that relies on the adapt-then-combine technique. FWI is a geophysical imaging technique that obtains high resolution images by exploiting the wave equation. In the proposed method, gradients based on the local error residual and local subsurface images are exchanged among neighboring agents. The proposed method shows that images close the global subsurface image can be obtained at each agent in the network via such cooperation.

**I want to give an oral presentation.:**

no

**I want to present a poster.:**

yes

## Poster Session / 13

**AI-based Evaluation of cardiac real-time MRI with congenital heart disease**

**Authors:** Alex Hoff<sup>1</sup>; Anja Bach<sup>1</sup>; Philipp Rosauer<sup>None</sup>; Darius A. Gerlach<sup>1</sup>; Jens Tank<sup>1</sup>; Wadim Koslow<sup>2</sup>

<sup>1</sup> *Institute of Aerospace Medicine, German Aerospace Center (DLR)*

<sup>2</sup> *Institute for Software Technology, German Aerospace Center (DLR)*

**Corresponding Author:** philipp.rosauer@dlr.de

Cardiac MRI is an important diagnostic tool in heart diseases for assessment of vital parameters. Current methods are limited to patients with regular heart beats and breath hold capability. New real-time MRI allows the recording of 2D slices of the pumping human heart during spontaneous breathing. Such high frame rates yield large amounts of data at different breath and cardiac phase. We introduce the key challenges in automated evaluations of this data especially in congenital heart diseases. These evaluations can be used to investigate the effect of respiration on parameters such as blood flow and stroke volume. The heart is acquired slice by slice, thus the cardiac cycles have to be synchronized to model a 3D heart model for in-phase value estimations. Another challenge is the anatomical segmentation. We present our workflow to tackle those challenges, show and discuss first results. One result is a breath- and cardiac cycle synchronized segmented univentricular heart in 4D.

**I want to give an oral presentation.:**

yes

**I want to present a poster.:**

yes

## Poster Session / 14

**Initial results using neuroimaging features to predict the genetic risk of RLS**

**Author:** Federico Raimondo<sup>1</sup>

**Co-authors:** Konrad Oexle<sup>2</sup>; Vera Komeyer<sup>3</sup>; Jan Kasper<sup>3</sup>; Sabrina Primus<sup>4</sup>; Juliane Winkelmann<sup>4</sup>; Simon Eickhoff<sup>3</sup>; Kaustubh Patil<sup>3</sup>

<sup>1</sup> *INM-7*

<sup>2</sup> *Institute of Neurogenomics (ING), HelmholtzZentrum München. München, Germany*

<sup>3</sup> *1. Institute of Neuroscience and Medicine, Brain and Behavior (INM-7), Forschungszentrum Jülich, Jülich, Germany.*

<sup>4</sup> *3. Institute of Neurogenomics (ING), HelmholtzZentrum München. München, Germany.*

**Corresponding Author:** f.raimondo@fz-juelich.de

Restless Legs Syndrome (RLS) is an urge to move the legs when at rest, resulting in severe insomnia and subsequent depression. While the ING at HMGU has deciphered a substantial part of the polygenic basis of RLS, there is still a lack of phenotypic and brain-derived biomarkers. Using the UKB database, we extracted gray matter volume, fractional amplitude of low-frequency fluctuation, global and local correlation from structural and functional MRI. From the genetic data, we extracted

the polygenic risk score (PRS) of RLS. We then created two machine learning models aimed to predict PRS from the brain-derived features.

So far, none of the learning algorithms was able to predict the PRS from the neuroimaging features. However, several relevant brain-derived markers have not been used yet. Despite preliminary negative results, the technical basis for large-scale analysis including neuroimaging and genetic data from the UKB database is now ready to be used for further enquiries.

**I want to give an oral presentation.:**

no

**I want to present a poster.:**

yes

16

## Using k-Means to identify Coronal Holes on AIA/SDO Images

**Authors:** Fadil Inceoglu<sup>None</sup>; Stefano Bianco<sup>1</sup>; Stephan Heinemann<sup>2</sup>; Yuri Shprits<sup>3</sup>

<sup>1</sup> *GFZ, Helmholtz Center Potsdam*

<sup>2</sup> *Max-Planck-Institute for Solar System Research, Goettingen, Germany*

<sup>3</sup> *GFZ*

**Corresponding Author:** stefano.bianco@gfz-potsdam.de

Through its magnetic activity, the Sun governs the conditions in Earth's vicinity, creating space weather events, which have drastic effects on our space- and ground-based technology. The identification of the coronal Holes on the Sun as one of the source regions of the solar wind is therefore crucial to achieve predictive capabilities. In this study, we used an unsupervised machine learning method, k-means, to pixel-wise cluster the passband images of the Sun in the wavelengths 171 Å, 193 Å, and 211 Å. Our results show that the pixel-wise k-means clustering together with systematic pre- and post-processing steps provides compatible results with those from complex methods, such as CNNs. More importantly, our study shows that there is a need for a CH database that a consensus about the CH boundaries are reached by observers independently. This database then can be used as the "ground truth", when using a supervised method or just to evaluate the goodness of the models.

**I want to give an oral presentation.:**

yes

**I want to present a poster.:**

yes

17

## Advances in landslide analysis using remote sensing: Results from Multisat4slows project

**Author:** Mahdi Motagh<sup>1</sup>

**Co-authors:** Aiyem Orynbaikyzy<sup>2</sup>; Daniel Eggert<sup>3</sup>; Simon Plank<sup>2</sup>; Mike Sips<sup>3</sup>; Magdalena Vassileva<sup>3</sup>; Wandu Wang<sup>3</sup>

<sup>1</sup> *GFz German Research Centre for Geosciences*

<sup>2</sup> *German Aerospace Centre (DLR)*

<sup>3</sup> *GFZ German Research Centre for Geosciences*

**Corresponding Author:** motagh@gfz-potsdam.de

In this presentation we summarize all the achievements that were made within the first year of the Multisat4slows project (Developing multi-scale satellite-based imaging platform for change detection: application for landslide hazard classification and early warning service), financed within the Helmholtz Imaging 2020 call. In particular, we introduce a new reference data base which has been compiled for training, testing and validating machine learning algorithms, discuss example applications on how various parameters extracted from SAR imagery improve change detection related to landslides, elaborate on our experience in using data-driven approaches for event timing detection, and finally introduce the first version of publicly available Data Analytics toolbox for rapid analysis of landslides, where the developed models are deployed.

**I want to give an oral presentation.:**

yes

**I want to present a poster.:**

no

19

## Helmholtz Imaging Modalities and Network

**Authors:** David Schwartz<sup>1</sup>; Philipp Heuser<sup>2</sup>; Franz Rhee<sup>3</sup>

<sup>1</sup> *DESY/IT*

<sup>2</sup> *HIP/DESY*

<sup>3</sup> *DESY*

**Corresponding Author:** philipp.heuser@desy.de

Scientists at the Helmholtz Association develop and apply a broad range of imaging modalities. The borders of hard- and software solutions for imaging are pushed to their limits and the respective scientists conduct cutting edge research across the scales. Imaging is the crucial method to study processes within atoms, molecules, organisms, ecosystems, and the universe. At Helmholtz Imaging Modalities we collect all the modalities, instruments, applications, and the respective scientific and engineering experts on one site.

Helmholtz Imaging Modalities is the heart of the Helmholtz Imaging Network. Get to know the imaging experts from the Helmholtz Association, explore the amazing portfolio of cutting edge instruments from satellites to synchrotrons. Helmholtz Imaging Modalities facilitates finding the right instruments, partners and collaborators for innovative projects, with just the right complementary expertise necessary to conduct research for grand challenges.

**I want to give an oral presentation.:**

no

**I want to present a poster.:**

yes

**Poster Session / 20**

## Performance Portable Reconstruction of Ptychography Data with the Alpaka C++ Library

**Authors:** Simeon Ehrig<sup>None</sup>; Jiri Vyskocil<sup>1</sup>

**Co-authors:** Silvio Achilles<sup>2</sup>; Nico Hoffmann<sup>3</sup>; Andreas Schropp<sup>4</sup>; Christian Schroer<sup>4</sup>; Dieter Weber<sup>5</sup>; Alexander Clausen<sup>5</sup>; Oleh Melnyk<sup>6</sup>; Knut Müller-Caspary<sup>5</sup>; Michael Bussmann<sup>1</sup>

<sup>1</sup> CASUS – Center for Advanced Systems Understanding, Helmholtz-Zentrum Dresden-Rossendorf e.V. (HZDR)

<sup>2</sup> DESY, Hamburg, Germany

<sup>3</sup> HZDR

<sup>4</sup> Center for X-ray and Nano Science CXNS, Deutsches Elektronen-Synchrotron DESY

<sup>5</sup> Forschungszentrum Jülich

<sup>6</sup> Helmholtz Zentrum München

**Corresponding Authors:** s.ehrig@hzdr.de, j.vyskocil@hzdr.de

Ptychography is a computational imaging method used to numerically retrieve the projection of an object from a set of measured diffraction patterns. Each diffraction pattern represents a partially overlapping area of the object. The corresponding inverse problem, i.e. the image reconstruction, can be solved by projection-based or gradient-based algorithms. However, existing implementations are usually optimized for a specific system and therefore difficult to port to new systems. To solve this problem, we will be introducing the alpaka library with a generic C++ interface to implement an algorithm one time and execute it on different target platforms, like CPUs and GPUs from different vendors. First, we ported an existing algorithm, implemented in CUDA C++, to alpaka to demonstrate the workflow and advantages. Then, we implemented another algorithm from scratch to obtain the software requirements for an easy and fast development cycle of alpaka based image reconstruction applications.

**I want to give an oral presentation.:**

no

**I want to present a poster.:**

yes

**Scientific Talks / 21**

## Computational Imaging for Art investigation and for Neuroscience

**Author:** Pier Luigi Dragotti<sup>1</sup>

<sup>1</sup> Imperial College London

In this talk we provide an overview of two research areas where computational imaging is likely to have an impact. We first focus on the heritage sector which is experiencing a digital revolution driven in part by the increasing use of non-invasive, non-destructive imaging techniques. These new imaging methods provide a way to capture information about an entire painting and can give us information about features at or below the surface of the painting. We focus on Macro X-Ray Fluorescence (XRF) scanning which is a technique for the mapping of chemical elements in paintings. After describing in broad terms the working of this device, a method that can process XRF scanning data from paintings is introduced. The results presented show the ability of our method to detect and separate weak signals related to hidden chemical elements in the paintings. We then discuss results on the Leonardo's "The Virgin of the Rocks" and show that our algorithm is able to reveal, more clearly than ever before, the hidden drawings of a previous composition that Leonardo then abandoned for the painting that we can now see. In the second part of the talk, we focus on

two-photon microscopy and neuroscience. Multi-photon microscopy is unparalleled in its ability to image cellular activity and neural circuits, deep in living tissue, at single-cell resolution. In this talk we introduce light-field two-photon microscopy and present a method to localize neurons in 3-D. The method is based on the use of proper sparsity priors, novel optimization strategies and machine learning.

**Panel Discussion / 22**

## Challenges for imaging. How do we deal with them?

**Guests:**

Prof. Otmar D. Wiestler (Helmholtz Association),  
Dr. Holger Becker (Member of the German Bundestag),  
Dr. Dagmar Kainmüller (MDC),  
Dr. Andrea Thorn (University Hamburg)

**I want to give an oral presentation.:**

**I want to present a poster.:**

**Intro / 23**

## Helmholtz Imaging

**Author:** Christian Schroer<sup>1</sup>

<sup>1</sup> *Helmholtz Imaging*

**Poster Session / 24**

## Poster Session

**UTILE project: Autonomous Image Analysis to Accelerate the Discovery and Integration of Energy Materials;** *Andre Colliard Granero*; IEK-13, FZJ

**PtyNAMi - Ptychographic Nano-Analytical Microscope;** *Andreas Schropp*; Center for X-ray and Nano Science CXNS, DESY

**Towards distributed imaging for autonomous seismic surveys in multi-agent networks;** *Ban-Sok Shin*; DLR

**In situ nanotomographic X-ray imaging of magnesium implant degradation;** *Berit Zeller-Plumhoff*; Hereon

**Correlative Microscopy of the Rhizosphere - Progress and Challenges;** *Chaturanga D. Bandara*; UFZ

**Initial results using neuroimaging features to predict the genetic risk of RLS;** *Federico Raimondo*; INM-7, FZJ

**Computational and machine learning approaches for the genetic analysis of histological images;** *Francesco Paolo Casale*; Helmholtz Munich

- Federated Learning for Data and Model Privacy in Cloud;** *Hussain Ahmad Madni*; University of Udine
- Mapping Arctic treeline vegetation using LiDAR data in the Mackenzie Delta area, Canada;** *Inge Günberg*; AWI
- Multi-axes fusing for uncertainty estimation and improved segmentation of biodegradable bone implants in SR $\mu$ CTs;** *Ivo Matteo Baltruschat*; Research and Innovation in Scientific Computing, DESY
- MRI reveals brain ventricle expansion in pediatric patients with acute disseminated encephalomyelitis;** *Jason Millward*; MDC
- Performance Portable Reconstruction of Ptychography Data with the Alpaka C++ Library;** *Jiri Vyskocil*; CASUS, HZDR
- Nuclear Verification from Space - Change Detection using Machine Learning and Sentinel-2 Imagery;** *Lisa Beumer*; FZJ
- MemBrain – Analysis of Membranes in Cryo-Electron Tomograms;** *Lorenz Lamm*; Helmholtz Munich
- Improving Explainability of Disentangled Representations using Multipath-Attribution Mappings;** *Lukas Klein*; Helmholtz Imaging
- 3D Imaging Modalities and Algorithms at the GINIX X-ray microscope;** *Markus Osterhoff*; Röntgenphysik Göttingen
- Improving convolutional neural network comprehensibility via interactive visualization of relevance maps: evaluation in Alzheimer’s disease;** *Martin Dyrba*; DZNE
- Partially coherent simulations of PETRA IV Beamlines;** *Martin Seyrich*; Center for X-ray and Nano Science CXNS, DESY
- Multi-dimensional imaging of solar cells with scanning X-ray microscopy;** *Michael Stuckelberger*; DESY
- Automatized Diffraction Pattern Recognition for Scanning Surface X-Ray Crystallography of Polycrystalline Materials;** *Nastasia Mukharamova*; DESY
- ObiWan-Microbi & MicrobeSeg: Deep-Learning Tools for Microbial Image Analysis;** *Oliver Neumann*; KIT
- Automatic Recognition of Dead Sea Geomorphological Features;** *Osama Alrabayah*; GEOMAR
- Object detection in dehazed Optical and Infrared Images;** *Oscar Hernan Ramírez Agudelo*; DLR
- The Hidden Image of Thawing Permafrost: project overview and first results of the radar polarimetric analysis;** *Paloma Saporta*; DLR
- Helmholtz Imaging Modalities;** *Philipp Heuser*; Helmholtz Imaging
- AI-based Evaluation of cardiac real-time MRI with congenital heart disease;** *Philipp Rosauer*; DLR
- How to classify single white blood cells in unseen data from different domains?;** *Raheleh Salehi*; Politecnico Di Torino
- Raw Image space improves Single-Cells Classification in Acute Myeloid Leukemia;** *Rao Muhammad Umer*; Institute of Computational Biology (ICB), Helmholtz Munich
- The Space-Filling Curve Needle;** *Sandro Elswijker*; German Aerospace Center (DLR)
- Simultaneous Mapping of Magnetic and Atomic Structure of Ferromagnets using Ltz-4D-STEM;** *Sangjun Kang*; KIT
- HistAuGAN: Style Transfer as Stain Augmentation Technique in Histopathology;** *Sophia Wagner*; Helmholtz AI

**Neuroimaging-Genetics bridge for better understanding of human brain organization;** *Talip Yasir Demirtas*; INM-7, FZJ

**DELAD: Deep Landweber-guided deconvolution with Hessian and sparse prior;** *Tomas Chobola*; Helmholtz Munich

**BaSiCPy: a napari plugin for microscopy illumination correction;** *Tingying Peng*; Helmholtz Munich

**Material-specific table-top EUV ptychography;** *Wilhelm Eschen*; Helmholtz Institut Jena

**DeStripe: A Self2Self Spatio-Spectral Graph Neural Network with Unfolded Hessian for Stripe Artifact Removal in Light-sheet Microscopy;** *Yu Liu*; Technische Universität Munich

**I want to give an oral presentation.:**

**I want to present a poster.:**

Scientific Talks / 25

## **Proposal of a Joint Inversion Imaging Approach for the Estimation of Brain Myelin Content using MRI**

**Author:** Ravi Dadsena<sup>1</sup>

<sup>1</sup> DZNE

Magnetic Resonance Imaging (MRI) is a useful method for detecting focal macroscopic tissue abnormalities in the brains of patients with neurodegenerative disorders. A variety of imaging techniques are commonly used to estimate the brain myelin content. Myelin water fraction (MWF) mapping using MRI has enabled researchers to directly examine myelination and demyelination in both developing and diseased brains. T1-, T2-, and T2\*-weighted multi-echo data have been proposed to estimate MWF in the human brain. Although, even for the relatively simple two pool signal models, consisting of myelin water and non-myelin associated water, the number of dimensions of the parameter space for acquiring MWF estimates remains high, which makes the parameter estimation challenging. The aim of this research is to improve the accuracy and precision of brain myelin content mapping. Utilizing geophysical joint inversion concepts, we propose a novel joint inversion imaging approach where data from multiple contrasts are combined in a single optimization process. When compared to state-of-the-art methods for MWF estimation, the proposed method is expected to be less biased and less susceptible to noise.

Scientific Talks / 26

## **Advances in landslide analysis using remote sensing: Results from Multisat4slows project**

**Author:** Mahdi Motagh<sup>1</sup>

<sup>1</sup> Helmholtz Centre Potsdam GFZ

In this presentation we summarize all the achievements that were made within the first year of the Multisat4slows project (Developing multi-scale satellite-based imaging platform for change detection: application for landslide hazard classification and early warning service), financed within the Helmholtz Imaging 2020 call. In particular, we introduce a new reference data base which has been



compiled for training, testing and validating machine learning algorithms, discuss example applications on how various parameters extracted from SAR imagery improve change detection related to landslides, elaborate on our experience in using data-driven approaches for event timing detection, and finally introduce the first version of publicly available Data Analytics toolbox for rapid analysis of landslides, where the developed models are deployed.

Scientific Talks / 27

## Deep Learning for Lithological Point Cloud Segmentation

Author: Ahmed J. Afifi<sup>1</sup>

<sup>1</sup> HZDR

Deep learning (DL) techniques are now ubiquitous in the field of computer vision and its various applications (classification, detection, and segmentation). Recent developments in 3D sensing technology and low-cost devices facilitate the process of 3D data collection. Light Detection and Ranging (LiDAR) and Structure from Motion (SfM) can rapidly generate centimeter to sub-centimeter resolution 3D point clouds, which are rapidly becoming essential to real-time applications such as autonomous driving and robotics. In Hyper 3D-AI project, we focus on solving the classification and segmentation tasks of multi-sensor 3D data using deep learning, i.e. the proposed methods would utilize different information that are acquired by the sensors to achieve a segmentation that is sensitive to geometric, textural and spectral attributes. We propose different deep models that can handle 3D data represented as point clouds and train them for the classification and segmentation tasks.

I want to give an oral presentation.:

I want to present a poster.:

Scientific Talks / 28

## Exploring Digital Twin of the Earth. Challenges in visualization of kilometer scale Earth System model simulations

Author: Nikolay Koldunov<sup>1</sup>

<sup>1</sup> AWI

The Earth's climate is changing, and science should provide better information about future climate change impacts on global and regional level. Current developments in High Performance Computing and Climate modelling, allow us to simulate the coupled Climate System with unprecedented level of detail, using spatial resolution of several kilometres in atmosphere and ocean. Those simulations, called Digital Twins of Earth (DTE), produce very large amounts of data that is hard to visualise and explore. We will discuss opportunities and challenges that come with emergence of DTE, including the need for new visualisation and analysis tools, image based data archiving and distribution as well as use of those data for educational and science communication purposes.

I want to give an oral presentation.:

I want to present a poster.:

## Scientific Talks / 29

## Deep-Learning Meets Microbial Live-Cell Imaging: Powerful Analysis Workflows from Annotation to Prediction

**Authors:** Bastian Wollenhaupt<sup>1</sup>; Johannes Seiffarth<sup>2</sup>

<sup>1</sup> FZJ

<sup>2</sup> Research Center Jülich

**Corresponding Author:** b.wollenhaupt@fz-juelich.de

Time-lapse microscopy in combination with precisely controllable microfluidic lab-on-a-chip systems allows observing the emergence of microbial populations starting from one single cell. Live-cell imaging is thus a powerful tool for studying heterogeneity of cell growth, morphological development, or cell-to-cell interaction. Such insights are door openers for predicting strain performances and engineering synthetic microbial cultures for industrial application. The key barrier to extracting spatiotemporal information from live-cell imaging experiments comprising hundreds of time-lapse image stacks each is an accurate and automated cell segmentation.

New deep-learning methods offer high quality and throughput for image processing of microbial time-lapses, scaling to hundreds of thousands of cells. To achieve top accuracy beyond specific imaging modalities and microbial morphologies, however, segmentation models require an enormous amount of ground truth data for training. Also, available approaches are difficult to handle due to heavy software and hardware dependencies. Within the SATOMI project, we developed two open access tools, *microbeSEG* and *ObiWan-Microbi*, that cover the full workflow of deep-learning methods in microfluidic live-cell analysis: *microbeSEG* facilitates the creation and management of ground-truth datasets and training of deep-learning segmentation, while *ObiWan-Microbi* provides a suite of semi-automated annotation tools and unlocks deep-learning execution in the cloud.

In our talk, we start with outlining the challenges arising in the analysis of large amounts of microfluidic image data from the different “user” and “developer” perspectives. We then present our deep-learning workflow for creating custom cell segmentation, which we showcase in action with a challenging example of a microbial consortia time-lapse imagery yielding results that were previously impossible to extract.

Although developed in the field of microbial live-cell imaging, the workflow is generally applicable whenever segmentation and image processing is employed.

**I want to give an oral presentation.:**

**I want to present a poster.:**

## Scientific Talks / 30

## Using k-Means to identify Coronal Holes on AIA/SDO Images

**Author:** Stefano Bianco<sup>1</sup>

<sup>1</sup> GFZ

Through its magnetic activity, the Sun governs the conditions in Earth’s vicinity, creating space weather events, which have drastic effects on our space- and ground-based technology. The identification of the coronal Holes on the Sun as one of the source regions of the solar wind is therefore crucial to achieve predictive capabilities. In this study, we used an unsupervised machine learning method, k-means, to pixel-wise cluster the passband images of the Sun in the wavelengths 171 Å, 193 Å, and 211 Å. Our results show that the pixel-wise k-means clustering together with systematic pre- and post-processing steps provides compatible results with those from complex methods, such

as CNNs. More importantly, our study shows that there is a need for a CH database that a consensus about the CH boundaries are reached by observers independently. This database then can be used as the “ground truth”, when using a supervised method or just to evaluate the goodness of the models.

**I want to give an oral presentation.:**

**I want to present a poster.:**

**Best Scientific Image Awards / 31**

## **Best Scientific Image Awards**

Participants Choice

**Scientific Talks / 32**

### **Metrics Reloaded – A new recommendation framework for biomedical image analysis validation**

**Author:** Paul Jäger<sup>1</sup>

<sup>1</sup> *Helmholtz Imaging*

Meaningful performance assessment of image analysis algorithms depends on objective and transparent performance metrics. Despite major shortcomings in the current state of the art, so far only limited attention has been paid to practical pitfalls associated with the use of particular metrics for an image analysis task. Therefore, a number of international initiatives have collaborated to provide researchers with guidance and tools for selecting performance metrics in a problem-aware manner. Based on input from experts from more than 60 institutions worldwide, we believe our metric recommendation framework to be useful to the community and to enhance the quality of image analysis algorithm validation.

**Scientific Talks / 33**

### **Multi-beam X-ray ptychography using coded probes**

**Author:** Mikhail Lyubomirskiy<sup>1</sup>

<sup>1</sup> *DESY*

Ptychography is a high-resolution imaging technique known for being capable of reaching sub-10 nm resolution. A coherent beam is required to reach this resolution. Currently, the coherent fraction of the beam for third-generation synchrotron sources is only 10%. Thus, ptychography needs to isolate the coherent flux. Consequently, more than 90% of the incoming X-rays are wasted. This reduces the total flux on the sample, which leads to an increased scan time or reduced spatial resolution due to a lower signal-to-noise ratio. The need to choose between high resolution and a large field of view is often a show stopper for many experiments. This problem is especially dire for biological samples, where a single specimen often is not representative of a population. The latest advances in ptychographic algorithms provide the possibility of introducing mutually incoherent

modes. This was adapted in recent developments for visible light microscopy with multiple independent beams. The sample is scanned simultaneously, not by one beam but by many, which can be mutually incoherent from each other. Each mode in the algorithm is used to reconstruct one beam and a corresponding region of the sample, expanding the scan area by the number of beams. We have successfully implemented this technique in the X-ray regime using up to 6 beams in parallel. Each beam was uniquely coded, which provided robust disentangling of the diffracted signal from different sample areas and thus artifact-free reconstructed object.

34

## Deep Learning for 3D Lithological Point Cloud Segmentation

**Authors:** Ahmed J M Afifi<sup>1</sup>; Sam T. Thiele<sup>1</sup>; Sandra Lorenz<sup>1</sup>; Richard Gloaguen<sup>1</sup>

<sup>1</sup> *Department of Exploration, Helmholtz-Institute Freiberg*

**Corresponding Author:** a.affi@hzdr.de

Deep learning (DL) techniques are now ubiquitous in the field of computer vision and its various applications (classification, detection, and segmentation). Recent developments in 3D sensing technology and low-cost devices facilitate the process of 3D data collection. Light Detection and Ranging (LiDAR) and Structure from Motion (SfM) can rapidly generate centimeter to sub-centimeter resolution 3D point clouds, which are rapidly becoming essential to real-time applications such as autonomous driving and robotics. In Hyper 3D-AI project, we focus on solving the classification and segmentation tasks of multi-sensor 3D data using deep learning, i.e. the proposed methods would utilize different information that are acquired by the sensors to achieve a segmentation that is sensitive to geometric, textural and spectral attributes. We propose different deep models that can handle 3D data represented as point clouds and train them for the classification and segmentation tasks.

**I want to give an oral presentation.:**

yes

**I want to present a poster.:**

no

**Intro / 36**

## Welcome and introduction

**Author:** Sara Krause-Solberg<sup>1</sup>

<sup>1</sup> *Helmholtz Imaging*

**Intro / 37**

## Mind the gap on bringing research and politics closer together

**Author:** Holger Becker<sup>1</sup>

<sup>1</sup> *Member of the German Bundestag*

38

## Looking to the future

**Authors:** Christian Schroer<sup>1</sup>; Sara Krause-Solberg<sup>2</sup>

<sup>1</sup> *Helmholtz Imaging*

<sup>2</sup> *HIP Helmholtz Imaging Platform, DESY*

**Corresponding Author:** sara.krause-solberg@desy.de

**I want to give an oral presentation.:**

**I want to present a poster.:**

Looking to the future / 39

## Next Big Challenges for Imaging Science

**Author:** Pier Luigi Dragotti<sup>1</sup>

<sup>1</sup> *Imperial College London*

**I want to give an oral presentation.:**

**I want to present a poster.:**

Looking to the future / 40

## AI for Imaging

**Corresponding Author:** dagmar.kainmueller@mdc-berlin.de

**I want to give an oral presentation.:**

**I want to present a poster.:**

Looking to the future / 41

## Big Data & Scalability

**I want to give an oral presentation.:**

**I want to present a poster.:**